

**Key Features:**

- Wide operating frequency range from 100 to 200MHz
- 1.0dB maximum insertion loss and 15dB minimum reverse isolation
- 50 ohm SMA female coaxial connectors
- 20 Watts CW forward power handling, 10 Watts reverse power termination
- Operating temperature range 0~+50°C
- Weight 310 grams (11 OZ)




**Description:**

F2323-0150-67S is a single junction lumped element type isolator with SMA female coaxial connectors operating in the frequency range from 100 to 200MHz. It offers 1.0dB maximum insertion loss and 15dB minimum reverse isolation. The coaxial isolator can handle 20 watts of forward CW power and 10 watts of reverse power.

**Electrical Specifications**





No.	Parameters	Units	Specifications		
			Minimum	Typical	Maximum
1	Frequency Range	MHz	100		200
2	Insertion Loss @ Room temp.	dB	-		1.0
3	Reverse Isolation @ room temp.	dB	15.0		
4	VSWR @ room temp.	-	-	-	1.50
5	Forward Power CW	Watts			20
6	Reverse Power CW	Watts			10
7	Operating Temperature	°C	0		+50
8	Impedance	Ω		50	
9	RF Connectors	-	SMA Female		
10	Signal Flow Direction	-	From Port 1 to Port 2		

**Mechanical Structure:**



Note: All units in inches (mm).

Typical Test Plots:



Revision History:

Revision	Date	Description	Comments
A00	06/16/2020	Initial Release	